



(12) **United States Patent**
Frey et al.

(10) **Patent No.:** **US 9,999,381 B2**
(45) **Date of Patent:** **Jun. 19, 2018**

(54) **DEVICE FOR PERFORMING AT LEAST ONE MEDICAL FUNCTION**

(71) Applicant: **Roche Diabetes Care, Inc.**,
Indianapolis, IN (US)

(72) Inventors: **Stephan-Michael Frey**, Griesheim
(DE); **Helmut Walter**, Heppenheim
(DE); **Jürgen Braun**, Ehningen (DE);
Jürgen Pfrang, Kallmünz (DE)

(73) Assignee: **ROCHE DIABETES CARE, INC.**,
Indianapolis, IN (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days. days.

(21) Appl. No.: **15/488,909**

(22) Filed: **Apr. 17, 2017**

(65) **Prior Publication Data**

US 2017/0215776 A1 Aug. 3, 2017

Related U.S. Application Data

(60) Division of application No. 14/614,548, filed on Feb.
5, 2015, now Pat. No. 9,655,551, which is a
(Continued)

(30) **Foreign Application Priority Data**

Aug. 27, 2010 (EP) 10174253

(51) **Int. Cl.**

A61B 5/145 (2006.01)
A61M 5/172 (2006.01)
A61B 5/1486 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 5/14532** (2013.01); **A61B 5/14865**
(2013.01); **A61M 5/1723** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC H01M 2/10; A61B 5/14532; A61B 5/1723;
A61B 5/14865; A61B 2560/0214; A61B
2560/0443

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,149,603 A 9/1992 Fleming et al.
5,938,640 A 8/1999 Maget et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101631579 A 1/2010
DE 10341093 A1 4/2005

Primary Examiner — Duane Smith

(74) *Attorney, Agent, or Firm* — Harness, Dickey

(57) **ABSTRACT**

A device for performing at least one medical function on a user is proposed. The device has at least one medical functional element that is designed to perform the medical function. The medical function is selected from a diagnostic, a therapeutic and a surgical function. The device has at least one evaluation and control part that comprises at least one actuation component for controlling the medical function. The evaluation and control part has at least one casing and at least one battery receptacle. The battery receptacle comprises at least one electrical energy reservoir, more particularly at least one battery. The battery receptacle is designed to be opened irreversibly by the user for removing the energy reservoir.

3 Claims, 2 Drawing Sheets

